



MAF

ON/OFF PORTABLE

- Portable line available in capacities 2.64 and 3.52 kW.
- Cooling only operation mode.



RC08B

PRODUCT ADVANTAGES


- 0.5 W in standby mode.
- Installation kit for window and wall as standard.
- Manual control integrated.
- Wireless remote control provided as standard.
- Self evaporative system.



MAF TECHNICAL DATA

Indoor units		AWPO-MAF009-C11	AWPO-MAF012-C11
COOLING			
Rated capacity	kW	2.64	3.52
Rated power input	kW	1.01	1.35
EER/Energy label		2.61/A	2.61/A
Operating limits	°C	17°/35° Dry bulb	
INDOOR UNIT			
Type		Monobloc	Monobloc
Sound Pressure level (LS/MS/HS)	dB(A)	46/49/52	46/49/52
Sound Power Level	dB(A)	65	65
Airflow	m³/h	370	370
Dehumidification	l/h	1.6	1.8
Outline dimensions (WxHxD)	mm	467x765x397	467x765x397
Package dimensions (WxHxD)	mm	517x880x437	517x880x437
Net weight/Gross weight	kg	30/34	33.5/37
Part number		7MB021056	7MB021057

FEATURES



AIRWELL SOLUTIONS

