wall mounted

ASYA18LE/24LC/30LC
ASYB24LD

CLASS A ALL DC

Optional
Wired R.C.

(18)

(24/30)

Stylish and slim, these elegant wall-mounted units complement any interior décor and are suitable for a variety of applications. The Fujitsu wall-mounted air conditioners include powerful cooling air outflows which gradually lower the room temperature to the required condition in the minimum time and at maximum efficiency.

- Slim-line construction
- Adjustable air flow
- Cooling/heating
- Ultra quiet
- Washable air filter
- Easy-to-use remote controller
- Quick and easy installation
- Long-life ion deodorisation filter options
- Plasma air filter options

ASYB09/12/18LD

CLASS A ALL DC

NEW

ASYA07LG/09LG/12LG/14LG

CLASS A ALL DC

Optional
Wired R.C.

FUJITSU
FUJITSU GENERAL partner

fge

		Inverter Heat Pump - R410A		
	Indoor	ASYA07LG	ASYA09LG	ASYA12LG
	Outdoor	AOYR07LG	AOYR09LG	AOYR12LG
Energy Label (Cooling / Heating)		A/A	A/A	A/A
Vertical Swing Flaps		✓	✓	✓
Auto Double Swing				
Auto Air Flow Adjustment		✓	✓	✓
Auto Restart		✓	✓	✓
Auto-Changeover		✓	✓	✓
10°C Heat Operation		✓	✓	✓
Economy Mode		✓	✓	✓
Sleep Timer		✓	✓	✓
Program Timer		✓	✓	✓
Long-life Ion Deodorisation Filter		✓	✓	✓
Apple-catechin Filter		✓	✓	✓
Coil Dry		✓	✓	✓
Washable Panel		✓	✓	✓
Nominal Capacity (kW)	Cooling	2.10 (0.50-3.00)	2.50 (0.50-3.20)	3.40 (0.90-3.90)
	Heating	3.00 (0.50-4.50)	3.20 (0.50-4.50)	4.00 (0.90-5.60)
Moisture Removal	l/h	1.00	1.30	1.80
Dimensions (HxWxD) mm	Inner	260x790x198	260x790x198	260x790x198
	Outer	540x660x290	540x660x290	540x660x290
Net Weight (kg)	Inner	8	8	8
	Outer	25	25	32
Room Air Circulation (high) m^3/h	Inner	750	750	750
	Outer	1720	1720	1830
Power Supply	V-PH-Hz	230/1/50	230/1/50	230/1/50
Power Supply To		Indoor	Indoor	Indoor
Running Current (A)	Cooling	2.50	3.20	4.30
	Heating	3.30	3.70	4.60
Starting Current	A	3.30	3.70	4.60
Fuse Rating	A	10	10	10
Power Consumption (kW)	Cooling	0.47	0.63	0.90
	Heating	0.66	0.75	0.97
Interconnecting Cable		3 + E	3 + E	3 + E
Remote Control Type		Wireless	Wireless	Wireless
Noise Levels (dB(A) Cooling)	Indoor Q/L/M/H	21 / 33 / 38 / 43	21 / 33 / 38 / 43	21 / 33 / 38 / 43
	Outdoor	45	45	48
Max Pipe Length	m	20	20	20
Max Height Difference	m	15	15	15
Refrigerant Charge	m	15	15	15
Pipe Size (inches)	Gas	3/8 (9.52mm)	3/8 (9.52mm)	3/8 (9.52mm)
	Liquid	1/4 (6.35mm)	1/4 (6.35mm)	1/4 (6.35mm)
Operating Range (°C)	Cooling	-10 ~ 43	-10 ~ 43	-10 ~ 43
	Heating	-15 ~ 24	-15 ~ 24	-15 ~ 24
Refrigerant		R410A	R410A	R410A

Optional Parts: Wired Remote Controller (UTB-YUD) for ASYA07-14LG (requires communication box kit), Wired Remote Controller (UTH-3TA16) for ASYA18LE, ASYA24LC and ASYA30LC Communication Box Kit (UTY-XCBXE), External Connect Kit (UTY-XWZX)

Inverter Heat Pump - R410A			
ASYA14LG	ASYA18LE	ASYA24LC	ASYA30LC
AOYR14LG	AOYR18LE	AOYR24LC	AOYR30LC
A/A	A/A	A/A	B/B
✓			
	✓	✓	✓
✓	✓	✓	✓
✓	✓	✓	✓
✓	✓	✓	✓
✓	✓		
✓			
✓	✓	✓	✓
✓	✓	✓	✓
✓	✓	✓	✓
✓	✓	✓	✓
✓	✓	✓	✓
✓	✓	✓	✓
4.00 (0.90-5.00)	5.20 (0.90-6.00)	7.10 (0.90-8.00)	8.00 (2.90-9.00)
5.00 (0.90-7.00)	6.30 (0.90-9.10)	8.10 (0.90-10.00)	9.00 (2.20-11.00)
2.10	2.80	3.00	3.40
260x790x198	320x998x228	320x998x228	320x998x228
620x790x298	620x790x298	578x790x315	830x900x330
8	14	14	14
41	41	44	62
800	900	1100	1100
2040	2070	2340	3600
230/1/50	230/1/50	230/1/50	230/1/50
Indoor	Outdoor	Outdoor	Outdoor
4.90	7.10	9.70	11.70
5.70	7.60	9.80	11.60
5.70	7.60	9.80	11.70
15	20	30	30
1.08	1.57	2.21 (0.11-2.62)	2.66 (0.58-3.60)
1.30	1.71	2.24 (0.11-3.68)	2.64 (0.50-4.30)
3 + E	3 + E	3 + E	3 + E
Wireless	Wireless	Wireless	Wireless
25 / 33 / 40 / 44	26 / 33 / 37 / 43	32 / 36 / 41 / 47	32 / 36 / 41 / 47
48	50	52	53
20	25	30	50
15	20	20	30
15	15	15	20
1/2 (12.70mm)	1/2 (12.70mm)	5/8 (15.88mm)	5/8 (15.88mm)
1/4 (6.35mm)	1/4 (6.35mm)	1/4 (6.35mm)	3/8 (9.52mm)
-10 ~ 43	-10 ~ 43	-10 ~ 43	-10 ~ 43
-15 ~ 24	-15 ~ 24	-15 ~ 24	-15 ~ 24
R410A	R410A	R410A	R410A

Only A /A rated systems are eligible for ECA (refer to the ECA website for confirmation)

For ASYA07/09/12LG

For ASYA14LG

For ASYA18LE

For ASYA24LC

For ASYA30LC

For ASYB09/12LD

For ASYB18/24LD

wall mounted (plasma)

		Inverter Heat Pump - R410A			
	Indoor	ASYB09LD	ASYB12LD	ASYB18LD	ASYB24LD
	Outdoor	AOYS09LD	AOYS12LD	AOYS18LD	AOYS24LD
Energy Label (Cooling / Heating)		A / A	A / A	B / A	A / A
Vertical Swing Flaps		✓	✓	✓	
Auto Double Swing					✓
Auto Air Flow Adjustment		✓	✓	✓	✓
Auto Restart		✓	✓	✓	✓
Auto-Changeover		✓	✓	✓	✓
Sleep Timer		✓	✓	✓	✓
Program Timer		✓	✓	✓	✓
Plasma Air Cleaner		✓	✓	✓	✓
Coil Dry		✓	✓	✓	✓
Washable Panel		✓	✓	✓	✓
Nominal Capacity (kW)	Cooling	2.60 (0.50-3.70)	3.50 (0.90-4.30)	5.20 (0.90-5.70)	7.10 (0.90-8.00)
	Heating	3.60 (0.50-6.10)	4.80 (0.90-6.70)	6.25 (0.90-9.10)	8.10 (0.09-10.60)
Moisture Removal	l/h	1.30	1.80	2.80	3.00
Dimensions (HxWxD) mm	Inner	283x790x230	283x790x230	283x790x230	320x998x228
	Outer	540x790x290	540x790x290	578x790x300	578x790x315
Net Weight (kg)	Inner	10	10	10	14
	Outer	34	36	40	44
Room Air Circulation (high) m^3/h	Inner	560	595	700	1170
	Outer	1970	1830	2000	2340
Power Supply	V-PH-Hz	230/1/50	230/1/50	230/1/50	230/1/50
Power Supply To		Indoor	Indoor	Indoor	Outdoor
Running Current (A)	Cooling	2.90	4.30	7.60	9.70
	Heating	3.90	5.60	7.70	9.80
Starting Current	A	3.90	5.60	7.70	9.80
Fuse Rating	A	10	10	20	30
Power Consumption (kW)	Cooling	0.61 (0.25-1.38)	0.91 (0.25-1.61)	1.72 (0.09-2.00)	2.21 (0.11-2.62)
	Heating	0.81 (0.25-1.96)	1.22 (0.25-2.30)	1.73 (0.09-2.66)	2.24 (0.11-3.68)
Interconnecting Cable		3 + E	3 + E	3 + E	3 + E
Remote Control Type		Wireless	Wireless	Wireless	Wireless*
Noise Levels (dB(A) Cooling)	Indoor Q/L/M/H	20 / 29 / 34 / 39	20 / 29 / 35 / 41	26 / 33 / 39 / 45	33 / 38 / 43 / 49
	Outdoor	47	47	50	52
Max Pipe Length	m	20	20	20	30
Max Height Difference	m	15	15	15	20
Refrigerant Charge	m	15	15	15	15
Pipe Size (inches)	Gas	3/8 (9.52mm)	3/8 (9.52mm)	1/2 (12.70mm)	5/8 (15.88mm)
	Liquid	1/4 (6.35mm)	1/4 (6.35mm)	1/4 (6.35mm)	1/4 (6.35mm)
Operating Range (°C)	Cooling	-10 ~ 43	-10 ~ 43	-10 ~ 43	-10 ~ 43
	Heating	-15 ~ 24	-15 ~ 24	-15 ~ 24	-15 ~ 24
Refrigerant		R410A	R410A	R410A	R410A

Optional Parts:

* Wired Remote Controller (UTH-3TA16) available for ASYB24LD only.

Only A / A rated systems are eligible for ECA (refer to ECA website for confirmation)

Distributed by:

The company reserves the right to make any variation in specification to the equipment described or to withdraw or replace products without prior notification or public announcement. All descriptions, Illustrations, drawings and specifications in this publication present only general particulars and shall not form any part of any contract. For full installation details please contact FG Eurofred or your local distributor.

Jan 2010

FG Eurofred Limited, Unit 150, Centennial Park, Elstree, Herts. WD6 3SG Tel 020 8731 3450 Fax 020 8731 3451